

2019 Hind Boots.

IN ANY CLASS THE FOLLOWING BOOT IS NOT PERMITTED



The following boot is permitted BUT ONLY IF BACK STRAP HAS BEEN REMOVED OR THE NEW MODEL IS BEING USED.



ALL RDS qualifiers and Young Horse Classes including IHB CLASSES

ALL HIND BOOTS IF WORN must be Young Horse type.

That is the following spec:

Maximum interior length of 16cms. And minimum exterior width of 5cms.

The inside of the protection must be smooth. Only non- elastic velcro fasteners are permitted; no hooks or any other fastening permitted.

The rounded rigid part of the protection must be placed around the inside of the fetlock.

No additional elements may be added or inserted onto the boot itself, other than a protective skirt, providing it is soft and clearly intended for protection only.

Fetlock rings may be used for protective purposes providing they are properly adjusted and providing the total weight on the horse's leg does not exceed 500 grams.

GENERAL PONY CLASSES

HIND BOOTS IF WORN

Ponies in classes up to and including 148 1.10m classes hind boots (if worn)MUST be Young Horse type. That is the following spec:

Maximum interior length of 16cms. And minimum exterior width of 5cms.

The inside of the protection must be smooth. Only non- elastic velcro fasteners are permitted; no hooks or any other fastening permitted.

The rounded rigid part of the protection must be placed around the inside of the fetlock.

No additional elements may be added or inserted onto the boot itself, other than a protective skirt, providing it is soft and clearly intended for protection only.

Ponies competing in 148 1.20M AND 1.30M CLASSES and horses inspecific CHILDREN ON HORSE CLASSES.

HIND BOOTS (if worn) AS WELL AS YOUNG HORSE TYPE BOOTS THE FOLLOWING BOOTS MAY BE WORN.

DOUBLE SHELL BOOTS (ie Boots with a protective element on inside and outside that wrap around the back of the fetlock) WITH STUD OR CLIP FASTNENINGS, WITH TWO ELASTIC STRAPS EACH OF MINIMUM WIDTH 2.5CMS.

HOWEVER The Mini double shell boots with one elastic strap minimum width 2.5cms and with stud or clip fastenings are also allowed.

THE INSIDE OF ALL BOOTS MUST BE SMOOTH.

NO VELCRO FASTENINGS ON ANY DOUBLE SHELL BOOT IN THE ABOVE CLASSES.

Fasteners must be one directional ie the fastner must be attached directly from one side of the boot to the other side; no mechanism permitting the fastener to double back on itself is permitted.

